

Technical Description

| | |
|-------------------------|---|
| WEIGHT | <ul style="list-style-type: none">• Side Right Single Door . Entry Single Door 50.110.440.320 : 508 Kg. |
| CRANE CARRY LOAD | <ul style="list-style-type: none">• 5 meters X 2 meters Maximum : 3 Ton. |
| SNOW LOAD | <ul style="list-style-type: none">• 2.10 kN/m² |
| WIND LOAD | <ul style="list-style-type: none">• Wind load strength in DIN EN 1991-1-4 Standards. |
| MATERIAL | <ul style="list-style-type: none">• S220 SE Z; 10241 and S250 GD Z; 10242 Skin-Pass galvanized stainless steel.<ul style="list-style-type: none">◦ Trapezoidal plate thickness: 0.6 mm◦ Profile thickness: 1.2 mm/2 mm• Mounting equipment, corner/roof sockets, and locking pins: Cathaphoresis surface coating.• Latch handle, flat bar, and roof eye bolt: MB, Hot-dip galvanized surface.• Door handle and hinge: Stainless steel.• Fastening equipment (rivet, screw, nut etc.): Stainless steel. |
| FLOOR | <ul style="list-style-type: none">• OSB/3 Panel is suitable for use in structural applications in humid areas in accordance with EN 300 Standards.• Panel Thickness: 15 mm• Load Carrying Capacity: 500 kg/m² Permissible Area Load• PMDI (Formaldehyde Free) Glue, Low Emission (E1)• Insect free conforming to IPPC Standards.• European construction material classification within the scope of EN 13501-1: D- s2, d0 suitable. |
| SECURITY | <ul style="list-style-type: none">• TSE - TÜV (GS-Mark) |
| SETUP | <ul style="list-style-type: none">• Installation is completed quickly and easily in 10 minutes by 3 personnel without the need for any tools.• 4 jack rings making it easy to carry.• Metal rails for forklift handling and floor ventilation.• Perfect Assembly Technology |
| DELIVERY | <ul style="list-style-type: none">• The container was packed in disassembled form and mounted with a mortise lock and core cylinder following DIN 18251-1 standards.• 12 locking pins, 2 sets of stainless door handles, and 1 key ring in the assembly box. |