

## Technical Description

<b>WEIGHT</b>	<ul style="list-style-type: none"> <li>• <b>30.110.440 – Side Right Single Door: 336 Kg.</b></li> </ul>
<b>CRANE HANDLING</b>	<ul style="list-style-type: none"> <li>• 3 Meters X 2 Meters - Maximum: 3 Tons.</li> </ul>
<b>SNOW LOAD</b>	<ul style="list-style-type: none"> <li>• 2.10 kN/m2</li> </ul>
<b>WIND LOAD</b>	<ul style="list-style-type: none"> <li>• Wind load strength in DIN EN 1991-1-4 Standards.</li> </ul>
<b>MATERIAL</b>	<ul style="list-style-type: none"> <li>• S220 GD Z; 1.0241 and S250 GD Z; 1.0242 Skin-Pass galvanized steel.               <ul style="list-style-type: none"> <li>o Trapezoidal plate thickness: 0,6 mm</li> <li>o Profile thickness: 1,2 mm/ 2 mm</li> </ul> </li> <li>• Corner/loof sockets: Aluminum 6082.</li> <li>• Latch handle, flat bar, roof eye bolt and locking pims: MB, Hot-dip galvanized surface.</li> <li>• Door handle and hinge: Stainless steel.</li> <li>• Fastening equipment (rivet, screw, nut etc.): Aluminum.</li> </ul>
<b>FLOOR</b>	<ul style="list-style-type: none"> <li>• OSB/3 Panel is suitable for use in structural applications in humid areas in accordance with EN 300 Standards.</li> <li>• Panel Thickness : 15 mm</li> <li>• Load Carrying Capacity: 500 kg/m2 Permissible Area Load</li> <li>• PMDI (Formaldehyde Free) Glue, Low Emission (E1)</li> <li>• Insect free conforming to IPPC Standards.</li> <li>• European construction material classification within the scope of EN 13501-1: D - s2, d0 suitable.</li> </ul>
<b>CERTIFICATION</b>	<ul style="list-style-type: none"> <li>• <b>ISO 9001/14001/50001 - TSE - TÜV (GS-Mark)</b> – Applications in progress.</li> </ul>
<b>SETUP</b>	<ul style="list-style-type: none"> <li>• Installation is completed quickly and easily in 5 minutes by 2 personel without the need any tools.</li> <li>• 4 jack rings making it easy to carry.</li> <li>• Metal rails for forklift handling and floor ventilation.</li> <li>• Perfect Assembly Technology</li> </ul>
<b>DELIVERY</b>	<ul style="list-style-type: none"> <li>• The container was packed in dissambled form with following DIN 18251-1 standards.</li> <li>• 10 locking pins, 1 set of stainless door handles, and 1 key ring in the assembly box.</li> </ul>