

Technical Description

| | |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEIGHT | <ul style="list-style-type: none"> • 60.110.320.331 - Entry Single Door . Opposite Double Door: 602 Kg. |
| CRANE HANDLING | <ul style="list-style-type: none"> • 6 Meters X 2 Meters - Maximum: 3 Tons. |
| SNOW LOAD | <ul style="list-style-type: none"> • 2.10 kN/m2 |
| WIND LOAD | <ul style="list-style-type: none"> • Wind load strength in DIN EN 1991-1-4 Standards. |
| MATERIAL | <ul style="list-style-type: none"> • S220 GD Z; 1.0241 and S250 GD Z; 1.0242 Skin-Pass galvanized steel. <ul style="list-style-type: none"> o Trapezoidal plate thickness: 0,6 mm o Profile thickness: 1,2 mm/ 2 mm • Corner/loof sockets: Aluminum 6082. • Latch handle, flat bar, roof eye bolt and locking pims: MB, Hot-dip galvanized surface. • Door handle and hinge: Stainless steel. • Fastening equipment (rivet, screw, nut etc.): Aluminum. |
| FLOOR | <ul style="list-style-type: none"> • OSB/3 Panel is suitable for use in structural applications in humid areas in accordance with EN 300 Standards. • Panel Thickness : 15 mm • Load Carrying Capacity: 500 kg/m2 Permissible Area Load • PMDI (Formaldehyde Free) Glue, Low Emission (E1) • Insect free conforming to IPPC Standards. • European construction material classification within the scope of EN 13501-1: D - s2, d0 suitable. |
| CERTIFICATION | <ul style="list-style-type: none"> • ISO 9001/14001/50001 - TSE - TÜV (GS-Mark) – Applications in progress. |
| SETUP | <ul style="list-style-type: none"> • Installation is completed quickly and easily in 10 minutes by 3 personel without the need any tools. • 4 jack rings making it easy to carry. • Metal rails for forklift handling and floor ventilation. • Perfect Assembly Technology |
| DELIVERY | <ul style="list-style-type: none"> • The container was packed in dissambled form with following DIN 18251-1 standards. • 14 locking pins, 2 set of stainless door handles, and 2 key ring in the assembly box. |