

Technical Description

WEIGHT	<ul style="list-style-type: none"> • 40.110.320 - Entry Single Door: 422 Kg.
CRANE HANDLING	<ul style="list-style-type: none"> • 4 Meters X 2 Meters - Maximum: 3 Tons.
SNOW LOAD	<ul style="list-style-type: none"> • 2.10 kN/m2
WIND LOAD	<ul style="list-style-type: none"> • Wind load strength in DIN EN 1991-1-4 Standards.
MATERIAL	<ul style="list-style-type: none"> • S220 GD Z; 1.0241 and S250 GD Z; 1.0242 Skin-Pass galvanized steel. <ul style="list-style-type: none"> o Trapezoidal plate thickness: 0,6 mm o Profile thickness: 1,2 mm/ 2 mm • Corner/loof sockets: Aluminum 6082. • Latch handle, flat bar, roof eye bolt and locking pims: MB, Hot-dip galvanized surface. • Door handle and hinge: Stainless steel. • Fastening equipment (rivet, screw, nut etc.): Aluminum.
FLOOR	<ul style="list-style-type: none"> • OSB/3 Panel is suitable for use in structural applications in humid areas in accordance with EN 300 Standards. • Panel Thickness : 15 mm • Load Carrying Capacity: 500 kg/m2 Permissible Area Load • PMDI (Formaldehyde Free) Glue, Low Emission (E1) • Insect free conforming to IPPC Standards. • European construction material classification within the scope of EN 13501-1: D - s2, d0 suitable.
CERTIFICATION	<ul style="list-style-type: none"> • ISO 9001/14001/50001 - TSE - TÜV (GS-Mark) – Applications in progress.
SETUP	<ul style="list-style-type: none"> • Installation is completed quickly and easily in 10 minutes by 3 personel without the need any tools. • 4 jack rings making it easy to carry. • Metal rails for forklift handling and floor ventilation. • Perfect Assembly Technology
DELIVERY	<ul style="list-style-type: none"> • The container was packed in dissambled form with following DIN 18251-1 standards. • 12 locking pins, 1 set of stainless door handles, and 1 key ring in the assembly box.