

Technical Description

WEIGHT	<ul style="list-style-type: none">• Side Left Single Door 30.110.450 : 336 Kg.
CRANE CARRY LOAD	<ul style="list-style-type: none">• 3 meters X 2 meters Maximum : 3 Ton.
SNOW LOAD	<ul style="list-style-type: none">• 2.10 kN/m²
WIND LOAD	<ul style="list-style-type: none">• Wind load strength in DIN EN 1991-1-4 Standards.
MATERIAL	<ul style="list-style-type: none">• S220 SE Z; 10241 and S250 GD Z; 10242 Skin-Pass galvanized stainless steel.<ul style="list-style-type: none">◦ Trapezoidal plate thickness: 0.6 mm◦ Profile thickness: 1.2 mm/2 mm• Mounting equipment, corner/roof sockets, and locking pins: Cathaphoresis surface coating.• Latch handle, flat bar, and roof eye bolt: MB, Hot-dip galvanized surface.• Door handle and hinge: Stainless steel.• Fastening equipment (rivet, screw, nut etc.): Stainless steel.
FLOOR	<ul style="list-style-type: none">• OSB/3 Panel is suitable for use in structural applications in humid areas in accordance with EN 300 Standards.• Panel Thickness: 15 mm• Load Carrying Capacity: 500 kg/m² Permissible Area Load• PMDI (Formaldehyde Free) Glue, Low Emission (E1)• Insect free conforming to IPPC Standards.• European construction material classification within the scope of EN 13501-1: D- s2, d0 suitable.
SECURITY	<ul style="list-style-type: none">• TSE - TÜV (GS-Mark)
SETUP	<ul style="list-style-type: none">• Installation is completed quickly and easily in 5 minutes by 2 personnel without the need for any tools.• 4 jack rings making it easy to carry.• Metal rails for forklift handling and floor ventilation.• Perfect Assembly Technology
DELIVERY	<ul style="list-style-type: none">• The container was packed in disassembled form and mounted with a mortise lock and core cylinder following DIN 18251-1 standards.• 10 locking pins, 1 set of stainless door handles, and 1 key ring in the assembly box.