

Technical Description

| | |
|----------------------|--|
| WEIGHT | <ul style="list-style-type: none">• 6050.110.450 – Side Left Single Door: 1025 Kg. |
| SNOW LOAD | <ul style="list-style-type: none">• 2.10 kN/m2 |
| WIND LOAD | <ul style="list-style-type: none">• Wind load strength in DIN EN 1991-1-4 Standards. |
| MATERIAL | <ul style="list-style-type: none">• S220 GD Z; 1.0241 and S250 GD Z; 1.0242 Skin-Pass galvanized steel.<ul style="list-style-type: none">o Trapezoidal plate thickness: 0,6 mmo Profile thickness: 1,2 mm/ 2 mm• Corner/loof sockets: Aluminum 6082.• Latch handle, flat bar, roof eye bolt and locking pims: MB, Hot-dip galvanized surface.• Door handle and hinge: Stainless steel.• Fastening equipment (rivet, screw, nut etc.): Aluminum. |
| FLOOR | <ul style="list-style-type: none">• OSB/3 Panel is suitable for use in structural applications in humid areas in accordance with EN 300 Standards.• Panel Thickness : 15 mm• Load Carrying Capacity: 500 kg/m2 Permissible Area Load• PMDI (Formaldehyde Free) Glue, Low Emission (E1)• Insect free conforming to IPPC Standards.• European construction material classification within the scope of EN 13501-1: D - s2, d0 suitable. |
| CERTIFICATION | <ul style="list-style-type: none">• ISO 9001/14001/50001 - TSE - TÜV (GS-Mark) – Applications in progress. |
| SETUP | <ul style="list-style-type: none">• Installation is completed quickly and easily in 10 minutes by 3 personel without the need any tools.• 4 jack rings making it easy to carry.• Metal rails for forklift handling and floor ventilation.• Perfect Assembly Technology |
| DELIVERY | <ul style="list-style-type: none">• The container was packed in dissambled form with following DIN 18251-1 standards.• 26 locking pins, 1 set of stainless door handles, and 1 key ring in the assembly box. |