



## Technical Description

|                      |  |
|----------------------|--|
| <b>WEIGHT</b>        | <ul style="list-style-type: none"><li>• <b>5040.110.320 - Entry Single Door: 868 Kg.</b></li></ul>   |
| <b>SNOW LOAD</b>     | <ul style="list-style-type: none"><li>• 2.10 kN/m2</li></ul>   |
| <b>WIND LOAD</b>     | <ul style="list-style-type: none"><li>• Wind load strength in DIN EN 1991-1-4 Standards.</li></ul>   |
| <b>MATERIAL</b>      | <ul style="list-style-type: none"><li>• S220 GD Z; 1.0241 and S250 GD Z; 1.0242 Skin-Pass galvanized steel.<ul style="list-style-type: none"><li>o Trapezoidal plate thickness: 0,6 mm</li><li>o Profile thickness: 1,2 mm/ 2 mm</li></ul></li><li>• Corner/loof sockets: Aluminum 6082.</li><li>• Latch handle, flat bar, roof eye bolt and locking pims: MB, Hot-dip galvanized surface.</li><li>• Door handle and hinge: Stainless steel.</li><li>• Fastening equipment (rivet, screw, nut etc.): Aluminum.</li></ul> |
| <b>FLOOR</b>         | <ul style="list-style-type: none"><li>• OSB/3 Panel is suitable for use in structural applications in humid areas in accordance with EN 300 Standards.</li><li>• Panel Thickness : 15 mm</li><li>• Load Carrying Capacity: 500 kg/m2 Permissible Area Load</li><li>• PMDI (Formaldehyde Free) Glue, Low Emission (E1)</li><li>• Insect free conforming to IPPC Standards.</li><li>• European construction material classification within the scope of EN 13501-1: D - s2, d0 suitable.</li></ul>                         |
| <b>CERTIFICATION</b> | <ul style="list-style-type: none"><li>• <b>ISO 9001/14001/50001 - TSE - TÜV (GS-Mark)</b> – Applications in progress.</li></ul>  |
| <b>SETUP</b>         | <ul style="list-style-type: none"><li>• Installation is completed quickly and easily in 10 minutes by 3 personel without the need any tools.</li><li>• 4 jack rings making it easy to carry.</li><li>• Metal rails for forklift handling and floor ventilation.</li><li>• Perfect Assembly Technology</li></ul>  |
| <b>DELIVERY</b>      | <ul style="list-style-type: none"><li>• The container was packed in dissambled form with following DIN 18251-1 standards.</li><li>• 24 locking pins, 1 set of stainless door handles, and 1 key ring in the assembly box.</li></ul>  |